

系统概览

1D/2D 条码扫描仪和 C5PC

连接电缆
M12, 在 RJ45 上为 8 针



ZCYV001 (直型)	2 m
ZCYV002 (直型)	5 m
ZCYV003 (直型)	10 m
ZCYV004 (弯型)	2 m
ZCYV005 (弯型)	5 m
ZCYV006 (弯型)	10 m
ZCYV007 (直型) *	2 m
ZCYV008 (直型) *	5 m
ZCYV009 (直型) *	10 m

连接线
M12, 在开放端为 12 针



ZDCL001 (直型) *	2 m
ZDCL002 (直型) *	5 m
ZDCL003 (直型) *	10 m
ZDCL007 (直型) *	30 m
ZDCL004 (弯型) *	2 m
ZDCL005 (弯型) *	5 m
ZDCL006 (弯型) *	10 m

紧固系统



WFIS03S12VA
ZNNZ003
ZNNC001

防护外壳



ZSV-02-01
ZSV-03-01

接口电缆
M12, 在 RS-232 上为 12 针




ZDCG003

连接电缆
M12, 在 12 针 M12 上为 12 针




ZDCV001*	2 m
ZDCV002*	5 m
ZDCV003*	10 m

接线盒




ZAA12NN01

转向镜



ZNNG028

遮挡玻璃



ZNNG053 备用防护罩
ZNNG054 扩散板
ZNNG055 偏振滤镜
ZNNG056 防护片 ESD
ZNNG057 激光防护片

图例

必要 配件
可选配件
适合拖链

*