

# Flow Sensor

## FFAF203


Part Number

UniFlow



- Display can be switched between flow and medium temperature
- Highest precision of its class
- Measurement independent of flow direction
- Selectable measuring range
- Temperature of the medium: 0 ... 100° C (140° C for 24 hours without current measurement)

wenglor UniFlow flow sensors measure the flow rate of aqueous and oily media in closed piping systems. UniFlow flow sensors are very easy to operate thanks to the integrated display. The highly visible switching status display enables the rapid localization of affected sensors for maintenance processes.



### Technical Data

#### Sensor-specific data

|                                           |              |
|-------------------------------------------|--------------|
| Measuring Range                           | 2...35 l/min |
| Setting Range                             | 4...35 l/min |
| Medium                                    | Water        |
| Measuring error (total)                   | 2 %          |
| MTTFd (EN ISO 13849-1)                    | 1194,55 a    |
| Switching Hysteresis                      | 5 %          |
| Temperature gradient                      | 30 K         |
| Response time in case of temperature jump | 10 s         |

#### Environmental conditions

|                                            |                     |
|--------------------------------------------|---------------------|
| Temperature of medium                      | 0...100 °C          |
| Temperature of the medium, short-term      | 140 °C              |
| Ambient temperature                        | -20...70 °C         |
| Pressure Resistance                        | 60 bar              |
| EMC                                        | DIN EN 60947-5-9    |
| Shock resistance per DIN IEC 68-2-27       | 30 g / 11 ms        |
| Vibration resistance per DIN IEC 60068-2-6 | 20 g (10...2000 Hz) |

#### Electrical Data

|                                             |              |
|---------------------------------------------|--------------|
| Supply Voltage                              | 16...32 V DC |
| Current Consumption (U <sub>b</sub> = 24 V) | 60 mA        |
| Number of Switching Outputs                 | 1            |
| Analog Output                               | 4...20 mA    |
| Signal source                               | Flow         |
| Response Time                               | 1...5 s      |
| Switching Output/Switching Current          | < 250 mA     |
| Switching Output Voltage Drop               | < 2 V        |
| Current Output Load Resistance              | < 500 Ohm    |
| Short Circuit Protection                    | yes          |
| Reverse Polarity Protection                 | yes          |
| Protection Class                            | III          |

#### Mechanical Data


|                                 |                        |
|---------------------------------|------------------------|
| Setting Method                  | Menu                   |
| Housing Material                | PBT; PC; FKM           |
| Material Control Panel          | Polyester              |
| Material in contact with media  | 1.4435; 1.4404; FKM    |
| Degree of Protection            | IP67 *                 |
| Connection                      | M12 × 1; 4-pin         |
| Process Connection              | Sealing cone M18 × 1,5 |
| Process Connection Length (PCL) | 64 mm                  |
| Probe Length (PL)               | 44 mm                  |

|                                   |           |
|-----------------------------------|-----------|
| Analog output flow                | ●         |
| PNP NO                            | ●         |
| Connection Diagram No.            | 533       |
| Control Panel No.                 | A21       |
| Suitable Connection Equipment No. | 2         |
| Suitable Mounting Technology No.  | 900   901 |

\* Certified by wenglor

### Complementary Products

Software




All dimensions in mm (1 mm = 0.03937 Inch)




## Ctrl. Panel

A21



01 = Switching Status Indicator  
20 = Enter key  
22 = Up key  
60 = display  
99 = Right button

533



### Legend

|           |                                            |           |                                |                                        |                     |
|-----------|--------------------------------------------|-----------|--------------------------------|----------------------------------------|---------------------|
| +         | Supply Voltage +                           | nc        | Not connected                  | ENBRS422                               | Encoder B/B (TTL)   |
| -         | Supply Voltage 0 V                         | U         | Test Input                     | ENA                                    | Encoder A           |
| ~         | Supply Voltage (AC Voltage)                | Ü         | Test Input inverted            | ENb                                    | Encoder B           |
| A         | Switching Output (NO)                      | W         | Trigger Input                  | AMIN                                   | Digital output MIN  |
| Ä         | Switching Output (NC)                      | W-        | Ground for the Trigger Input   | AMAX                                   | Digital output MAX  |
| V         | Contamination/Error Output (NO)            | O         | Analog Output                  | AOK                                    | Digital output OK   |
| Ÿ         | Contamination/Error Output (NC)            | O-        | Ground for the Analog Output   | SY In                                  | Synchronization In  |
| E         | Input (analog or digital)                  | BZ        | Block Discharge                | SY OUT                                 | Synchronization OUT |
| T         | Teach Input                                | Amv       | Valve Output                   | OLT                                    | Brightness output   |
| Z         | Time Delay (activation)                    | a         | Valve Control Output +         | M                                      | Maintenance         |
| S         | Shielding                                  | b         | Valve Control Output 0 V       | rsv                                    | Reserved            |
| RxD       | Interface Receive Path                     | SY        | Synchronization                | Wire Colors according to DIN IEC 60757 |                     |
| TxD       | Interface Send Path                        | SY-       | Ground for the Synchronization | BK                                     | Black               |
| RDY       | Ready                                      | E+        | Receiver-Line                  | BN                                     | Brown               |
| GND       | Ground                                     | S+        | Emitter-Line                   | RD                                     | Red                 |
| CL        | Clock                                      | ±         | Grounding                      | OG                                     | Orange              |
| E/A       | Output/Input programmable                  | SnR       | Switching Distance Reduction   | YE                                     | Yellow              |
| IO-Link   | IO-Link                                    | Rx+/-     | Ethernet Receive Path          | GN                                     | Green               |
| PoE       | Power over Ethernet                        | Tx+/-     | Ethernet Send Path             | BU                                     | Blue                |
| IN        | Safety Input                               | Bus       | Interfaces-Bus A(+)/B(-)       | VT                                     | Violet              |
| OSSD      | Safety Output                              | La        | Emitted Light disengageable    | GY                                     | Grey                |
| Signal    | Signal Output                              | Mag       | Magnet activation              | WH                                     | White               |
| BL_D+/-   | Ethernet Gigabit bidirect. data line (A-D) | RES       | Input confirmation             | PK                                     | Pink                |
| ENo RS422 | Encoder 0-pulse 0/Ü (TTL)                  | EDM       | Contact Monitoring             | GNYE                                   | Green/Yellow        |
| PT        | Platinum measuring resistor                | ENARIS422 | Encoder A/A (TTL)              |                                        |                     |