
wenglor
the innovative family

Technical Data

ZAS35R501
Connection Line

M12 × 1; 5-pin



c UL us LISTED
IND. CONT. EQ
72HL / E189727
For use in class 2 circuits

EN


Dimensions in mm
Subject to change without notice
Version 0
www.wenglor.com

Technical data

Mechanical Data	
Connection 1	Socket, straight
Connection mode 1	M12 × 1, 5-pin
Connection 2	stripped
Torque	M12: 0,6 Nm
Coding	A-coding
Cable length (L)	5 m
Outer diameter (d)	5 mm
Wire cross-section	0.34 mm²
Degree of Protection	IP67
Temperature Range	-25...80 °C
Cable Jacket Material	Plastic, PUR
Material Wire Insulation	Plastic, PP
Material Sleeve Nut	Brass, nickel-plated
Halogen-free	yes
Drag Chain Suitable	yes
Bending radius (fixed installation)	5 × d
Bending radius (used in motion)	10 × d
Travel speed (with 5 m horizontal travel distance)	≤ 3,3 m/s
Acceleration	≤ 5 m/s²
Bending cycles	≤ 5000000

General Data	
Scope of delivery	1 × line
Packaging unit	1 Piece

Technical illustrations



Pin	Wire color
1	Brown
2	White
3	Blue
4	Black
5	Gray