

# Retro-Reflex Sensor

## LM89PCV2

Part Number




- Low-cost
- Switching distance adjuster

### Technical Data


Optical Data	
Range	6500 mm
Reference Reflector/Reflex Foil	RQ100BA
Switching Hysteresis	< 15 %
Light Source	Red Light
Polarization Filter	yes
Service Life (T = +25 °C)	100000 h
Max. Ambient Light	10000 Lux
Opening Angle	5 °
Two-Lens Optic	yes
Electrical Data	
Supply Voltage	10...30 V DC
Current Consumption (U <sub>b</sub> = 24 V)	< 40 mA
Switching Frequency	1 kHz
Response Time	500 μs
Temperature Drift	< 10 %
Temperature Range	-10...60 °C
Switching Output Voltage Drop	< 2,5 V
PNP Switching Output/Switching Current	200 mA
Residual Current Switching Output	< 50 μA
Short Circuit Protection	yes
Reverse Polarity Protection	yes
Overload Protection	yes
Protection Class	III
Mechanical Data	
Setting Method	Potentiometer
Housing Material	Plastic
Full Encapsulation	yes
Degree of Protection	IP67
Connection	M12 × 1; 4-pin
Contamination Output	●
PNP NO/NC switchable	●
Connection Diagram No.	105
Control Panel No.	M2
Suitable Connection Technology No.	2
Suitable Mounting Technology No.	360

A reflector must be used in combination with these sensors. They can be installed in all kinds of industrial environments thanks to ample functional reserve. Even reflective objects can be reliably recognized through the use of polarized light.




### Complementary Products


PNP-NPN Converter BG2V1P-N-2M  
 Protection Housing Set ZSM-NN-02  
 Protection Housing ZSV-0x-01  
 Reflector, Reflex Foil



## Ctrl. Panel



05 = Switching Distance Adjuster  
08 = NO/NC Switch  
30 = Switching Status/Contamination Warning



## Legend

+	Supply Voltage +	PT	Platinum measuring resistor	ENa	Encoder A
-	Supply Voltage 0 V	nc	not connected	ENb	Encoder B
~	Supply Voltage (AC Voltage)	U	Test Input	AMIN	Digital output MIN
A	Switching Output (NO)	U	Test Input inverted	AMAX	Digital output MAX
Ā	Switching Output (NC)	W	Trigger Input	AOK	Digital output OK
V	Contamination/Error Output (NO)	O	Analog Output	SY In	Synchronization In
Ṽ	Contamination/Error Output (NC)	O-	Ground for the Analog Output	SY OUT	Synchronization OUT
E	Input (analog or digital)	BZ	Block Discharge	LI	Brightness output
T	Teach Input	AWV	Valve Output	M	Maintenance
Z	Time Delay (activation)	a	Valve Control Output +		
S	Shielding	b	Valve Control Output 0 V		
RxD	Interface Receive Path	SY	Synchronization		
TxD	Interface Send Path	E+	Receiver-Line		
RDY	Ready	S+	Emitter-Line		
GND	Ground	±	Grounding		
CL	Clock	SnR	Switching Distance Reduction		
E/A	Output/Input programmable	Rx+/-	Ethernet Receive Path		
IO-Link	IO-Link	Tx+/-	Ethernet Send Path		
PoE	Power over Ethernet	Bus	Interfaces-Bus A(+)/B(-)		
IN	Safety Input	La	Emitted Light disengageable		
OSSD	Safety Output	Mag	Magnet activation		
Signal	Signal Output	RES	Input confirmation		
BI-D+/-	Ethernet Gigabit bidirect. data line (A-D)	EDM	Contactor Monitoring		
EN0 RS422	Encoder 0-pulse 0-0 (TTL)	ENAS422	Encoder A/A (TTL)		
		ENBS422	Encoder B/B (TTL)		

## Wire Colors according to DIN IEC 757

BK	Black
BN	Brown
RD	Red
OG	Orange
YE	Yellow
GN	Green
BU	Blue
VT	Violet
GY	Grey
WH	White
PK	Pink
GNYE	Green/Yellow

## Feasible reflector distance

Reflector type, mounting distance

RQ100BA	0,04...6,5 m	RR25KP	0,14...1 m
RE18040BA	0,12...3 m	RR21_M	0,14...1,9 m
RQ84BA	0,06...5 m	ZRAE02B01	0,15...2,5 m
RR84BA	0,06...4,5 m	ZRME01B01	0,2...0,9 m
RE9538BA	0,12...1,5 m	ZRME03B01	0,2...2,3 m
RE6151BM	0,14...4 m	ZRMR02K01	0,16...1 m
RR50_A	0,03...3,3 m	ZRMS02_01	0,2...1 m
RE6040BA	0,05...4 m	RF505	0,19...1,5 m
RE8222BA	0,08...2 m	RF508	0,21...1,4 m
RR34_M	0,16...2,2 m	RF258	0,31...1,4 m
RE3220BM	0,2...1,5 m	ZRDF03K01	0,16...4 m
RE6210BM	0,2...1,7 m	ZRDF10K01	0,16...4,5 m
RR25_M	0,15...1,8 m		

