

Control Unit

uniVision Image Extended

BB1C504

Part Number



- Compact housing in 86 × 227 × 260 mm format
- Configurable uniVision software for evaluating images from machine vision cameras
- Control unit with uniVision Image Extended software installed
- Wear and noise reduction thanks to passive, fanless cooling

The control unit is a CPU for evaluating data from image processing products. Its compact design ensures the necessary flexibility for easy, space-saving installation, for example in a control cabinet or on a wall. Quick initial start-up is made possible by the pre-installed software. Various standard interfaces are available for the output of results. An extensive range of optional accessories is also available including monitor, keyboard and switch.

Technical Data

Electrical Data

Supply Voltage	9...48 V DC
Current Consumption (U _b = 24 V)	< 5 A
Temperature Range	0...45 °C
Number of RJ45 Industrial Ethernet ports	2
Number of USB 2.0 interfaces	2
Number of USB 3.0 interfaces	6
Number of Gigabit Ethernet RJ45	2
Number of display port interfaces	2
Number of VGA ports	1
Number of HDMI ports	1
Number of PS/2 ports	1

Mechanical Data

Housing Material	Aluminum, anodised
Degree of Protection	IP40
Wall mounting	yes
Software	uniVision Image Extended
Processor	Intel® Core i7
Clock Frequency	4,4 GHz
RAM	16 GB
Hard disk	128 GB SSD

Ethernet	●
PROFINET-I/O, CC-C	●
EtherNet/IP™	●
USB Interface	●
PS/2 (mouse/key pad)	●
VGA Connection	●
Display port connection	●

Complementary Products

BBZK machine vision camera
Control unit license upgrade
EHSS001 Switch
Key Pad Z0044
Monitor ZNNG026

