wenglor
the innovative family


Technical Data

P1PC382

Laser Distance Sensor

Triangulation





Symbol	Key
1	Emitter diode
2	Receiver diode
3	Switching status indicator O2
4	Power LED
5	Switching status indicator O1
6	Teach-in button

EN

Dimensions in mm
Subject to change without notice
Version 0
www.wenglor.com

Technical data

Optical Data	
Working Range	60...660 mm
Setting Range	60...660 mm
Switching Hysteresis	< 1 %
Light Source	Laser, red
Wavelength	655 nm
Service Life (T = +25 °C)	100000 h
Laser Class (EN 60825-1)	1
Max. Ambient Light	10000 Lux
Light Spot Diameter	see table 1

Electrical Data	
Supply Voltage	18...30 V DC
Current Consumption (Ub = 24 V)	< 30 mA
Switching Frequency	650 Hz
Response Time	< 0.77 ms
Temperature Drift	< 150 µm/K
Temperature Range	-25...60 °C
Number of Switching Outputs	1
Switching Output Voltage Drop	< 1.5 V
Switching Output/Switching Current	100 mA
Short Circuit Protection	yes
Reverse Polarity Protection	yes
Overload Protection	yes
Interface	IO-Link V1.1
IO-Link Version	1.1.4
IO-Link transmission speed	COM3
Protection Class	III
FDA Accession Number	2512215-000

Mechanical Data	
Setting Method	Teach-In NFC
Housing Material	Plastic, ABS
Degree of Protection	IP67 IP68
Connection Type	Plug variant
Connection	M12 × 1; 5-pin
Optic Cover	Plastic, PMMA

Safety-relevant Data	
MTTFd (EN ISO 13849-1)	821.68 a


General Data	
Scope of delivery	1 × Z1PE002 mounting set 1 × initial start-up instructions 1 × sensor

Adjustable parameters	
Output	Error Output Push-pull NPN PNP
Circuit	NC NO NC+NO
Other parameters	Exposure time Laser light Switching hysteresis Teach-in mode Off-delay On-delay

All other parameters can be found in the product documentation.

BMECat data	
eCl@ss 5.1.4	27-27-09-04 Light scanner w. background masking
eCl@ss 6.x	27-27-09-04 Light scanner w. background masking
eCl@ss 7.0	27-27-09-04 Light scanner w. background masking
eCl@ss 7.1	27-27-09-04 Light scanner w. background masking
eCl@ss 8.x	27-27-09-04 Light scanner w. background masking
eCl@ss 10.0.1	27-27-09-04 Light scanner w. background masking

Technical illustrations



Pin	Pin function	Polarity	Circuit
1	Supply Voltage +		
2	Switching Output 2	NPN	Antivalent
3	Supply voltage 0 V		
4	Switching Output 1 IO-Link	NPN	NO
5	Switchable emitted light	High active	

Table 1			
Working Distance	60 mm	360 mm	660 mm
Spot Size	1,5 × 3,5 mm	1,3 × 5 mm	1,1 × 6,7 mm