

Pressure Sensor

FFMP213

Part Number


UniBar



- Highly visible output indicator
- Simple operation via the display

UniBar pressure sensors measure the relative pressure in closed systems of any medium in the range -1...600 bar.

UniBar pressure sensors are very easy to use thanks to the integrated display. The highly visible switching status display enables the rapid localization of affected sensors for maintenance processes.




Technical Data

Sensor-specific data	
Measuring Range	0...600 bar
Measurement Type	relative
Maximum overload pressure	1200 bar
Bursting pressure	1600 bar
Setting Range	4...100 %
Medium	Liquids, gases
Switching Hysteresis	2 %
Measuring error	< ± 0,5 %
Temperature Drift	0,025 %/K
Environmental conditions	
Temperature of medium	-25...80 °C
Ambient temperature	-25...80 °C
EMC	DIN EN 61326-2-3
Shock resistance per DIN IEC 68-2-27	30 g / 11 ms
Vibration resistance per DIN IEC 60068-2-6	20 g (10...2000 Hz)
Electrical Data	
Supply Voltage	16...32 V DC
Current Consumption (Ub = 24 V)	< 60 mA
Number of Switching Outputs	2
Response Time	30 ms
Switching Output/Switching Current	< 250 mA
Switching Output Voltage Drop	< 2 V
Resolution	10 bit
Short Circuit Protection	yes
Reverse Polarity Protection	yes
Protection Class	III
Mechanical Data	
Setting Method	Menu
Housing Material	PBT; PC; FKM
Material Control Panel	Polyester
Material in contact with media	1.4435; 1.4404
Degree of Protection	IP67 *
Connection	M12 × 1; 4-pin
Process Connection	G 1/2"

PNP NO	●
Connection Diagram No.	536
Control Panel No.	A05
Suitable Connection Equipment No.	2


* Certified by wenglor




All dimensions in mm (1 mm = 0.03937 Inch)

Ctrl. Panel

A05



01 = Switching Status Indicator
20 = Enter key
22 = Up key
60 = display
99 = Right button



Legend							
+	Supply Voltage +	nc	Not connected	ENBRS422	Encoder B/B (TTL)		
-	Supply Voltage 0 V	U	Test Input	ENA	Encoder A		
~	Supply Voltage (AC Voltage)	Ü	Test Input inverted	ENb	Encoder B		
A	Switching Output (NO)	W	Trigger Input	AMIN	Digital output MIN		
Ā	Switching Output (NC)	W-	Ground for the Trigger Input	AMAX	Digital output MAX		
V	Contamination/Error Output (NO)	O	Analog Output	AOK	Digital output OK		
Ȳ	Contamination/Error Output (NC)	O-	Ground for the Analog Output	SY In	Synchronization In		
E	Input (analog or digital)	BZ	Block Discharge	SY OUT	Synchronization OUT		
T	Teach Input	Amv	Valve Output	OLt	Brightness output		
Z	Time Delay (activation)	a	Valve Control Output +	M	Maintenance		
S	Shielding	b	Valve Control Output 0 V	rsv	Reserved		
RxD	Interface Receive Path	SY	Synchronization	Wire Colors according to DIN IEC 60757			
TxD	Interface Send Path	SY-	Ground for the Synchronization	BK	Black		
RDY	Ready	E+	Receiver-Line	BN	Brown		
GND	Ground	S+	Emitter-Line	RD	Red		
CL	Clock	±	Grounding	OG	Orange		
E/A	Output/Input programmable	SnR	Switching Distance Reduction	YE	Yellow		
IO-Link	IO-Link	Rx+/-	Ethernet Receive Path	GN	Green		
PoE	Power over Ethernet	Tx+/-	Ethernet Send Path	BU	Blue		
IN	Safety Input	Bus	Interfaces-Bus A(+)/B(-)	VT	Violet		
OSSD	Safety Output	La	Emitted Light disengageable	GY	Grey		
Signal	Signal Output	Mag	Magnet activation	WH	White		
BL_D+/-	Ethernet Gigabit bidirect. data line (A-D)	RES	Input confirmation	PK	Pink		
ENo RS422	Encoder 0-pulse 0/Ü (TTL)	EDM	Contact Monitoring	GNYE	Green/Yellow		
PT	Platinum measuring resistor	ENARIS422	Encoder A/A (TTL)				