

Pressure Sensor

FX6P202

Part Number

weFlux² InoxSens



- Analog output: 4...20 mA
- Compact, laser-welded stainless steel 316L housing
- Very fast response time of < 1 s

Technical Data

Sensor-specific data	
Measuring Range	-1...25 bar
Measurement Type	relative
Maximum overload pressure	50 bar
Bursting pressure	75 bar
Medium	Liquids, gases
Pressure response time (t90)	< 1 ms
Measuring error (total)	≤ ± 1 %
Environmental conditions	
Temperature of medium	-25...125 °C**
Ambient temperature	-25...80 °C
Atmospheric humidity	100% r.h.
Storage temperature	-25...80 °C
EMC	DIN EN 61326-2-3
Shock resistance per DIN IEC 68-2-27	50 g / 11 ms
Vibration resistance per DIN IEC 60068-2-6	10 g (10...2000 Hz)
Electrical Data	
Supply Voltage	9...28 V DC
Current Consumption (U _b = 24 V)	< 21 mA
Number of analog outputs	1
Analog Output	4...20 mA
Signal source	Pressure
Current Output Load Resistance	< 500 Ohm
Short Circuit Protection	yes
Reverse Polarity Protection	yes
Protection Class	III
Mechanical Data	
Sensor element	Stainless steel membrane
Housing Material	1.4404
Material in contact with media	1.4404; 1.4548; FKM
Degree of Protection	IP68/IP69K *
Connection	M12 × 1; 4-pin
Process Connection	G 1/2"
Seal material	FKM
Safety-relevant Data	
MTTFd (EN ISO 13849-1)	3283,16 a
Analog Output	●
Connection Diagram No.	142
Suitable Connection Equipment No.	2
Suitable Mounting Technology No.	903


* Not UL certified

** Sensors up to 125 °C medium temperature suitable. During installation, please ensure that the sensor housing is sufficiently cooled by the surroundings.





27



Legend					
+	Supply Voltage +	nc	Not connected	ENB ^{RS422}	Encoder B/B ⁺ (TTL)
-	Supply Voltage 0 V	U	Test Input	ENa	Encoder A
~	Supply Voltage (AC Voltage)	Ü	Test Input inverted	ENb	Encoder B
A	Switching Output (NO)	W	Trigger Input	AMIN	Digital output MIN
Ä	Switching Output (NC)	W-	Ground for the Trigger Input	AMAX	Digital output MAX
V	Contamination/Error Output (NO)	O	Analog Output	AOK	Digital output OK
ȳ	Contamination/Error Output (NC)	O-	Ground for the Analog Output	SY In	Synchronization In
E	Input (analog or digital)	BZ	Block Discharge	SY OUT	Synchronization OUT
T	Teach Input	AMv	Valve Output	OLt	Brightness output
Z	Time Delay (activation)	a	Valve Control Output +	M	Maintenance
S	Shielding	b	Valve Control Output 0 V	rsv	Reserved
RxD	Interface Receive Path	SY	Synchronization	Wire Colors according to DIN IEC 60757	
TxD	Interface Send Path	SY-	Ground for the Synchronization		
RDY	Ready	E+	Receiver-Line	BK	Black
GND	Ground	S+	Emitter-Line	BN	Brown
CL	Clock	±	Grounding	RD	Red
E/A	Output/Input programmable	SnR	Switching Distance Reduction	OG	Orange
	IO-Link	Rx+/-	Ethernet Receive Path	YE	Yellow
PoE	Power over Ethernet	Tx+/-	Ethernet Send Path	GN	Green
IN	Safety Input	Bus	Interfaces-Bus A(+)/B(-)	BU	Blue
QSSD	Safety Output	La	Emitted Light disengageable	VT	Violet
Signal	Signal Output	Mag	Magnet activation	GY	Grey
BI_Dx/-	Ethernet Gigabit bidirect. data line (A-D)	RES	Input confirmation	WH	White
EN ^{RS422}	Encoder 0-pulse 0/Ü (TTL)	EDM	Contact Monitoring	PK	Pink
PT	Platinum measuring resistor	EN ^{RS422}	Encoder A/A ⁺ (TTL)	GNYE	Green/Yellow