

# Inductive Sensor

with Standard Switching Distances

## IJ008BE35VB1

Part Number



### Technical Data

#### Inductive Data

|                                                |                |
|------------------------------------------------|----------------|
| Switching Distance                             | 0,8 mm         |
| Correction Factors Stainless Steel V2A/CuZn/Al | 0,68/0,45/0,36 |
| Mounting                                       | Flush          |
| Mounting A/B/C/D in mm                         | 0/4/2,4/0      |
| Switching Hysteresis                           | < 15 %         |

#### Electrical Data

|                                             |              |
|---------------------------------------------|--------------|
| Supply Voltage                              | 10...30 V DC |
| Current Consumption (U <sub>b</sub> = 24 V) | < 10 mA      |
| Switching Frequency                         | 5 kHz        |
| Temperature Drift                           | < 10 %       |
| Temperature Range                           | -25...80 °C  |
| Switching Output Voltage Drop               | < 1 V        |
| Switching Output/Switching Current          | 100 mA       |
| Residual Current Switching Output           | < 100 µA     |
| Short Circuit Protection                    | yes          |
| Reverse Polarity and Overload Protection    | yes          |
| Protection Class                            | III          |

#### Mechanical Data

|                      |                                        |
|----------------------|----------------------------------------|
| Housing Material     | Stainless steel, V2A<br>(1.4305 / 303) |
| Sensing face         | Plastic, PA                            |
| Full Encapsulation   | yes                                    |
| Degree of Protection | IP67                                   |
| Connection           | M5 × 0,5; 4-pin                        |

#### Safety-relevant Data

|                        |           |
|------------------------|-----------|
| MTTFd (EN ISO 13849-1) | 5680,48 a |
| Packaging unit         | 1 Piece   |

PNP NO



Connection Diagram No.


1021

Suitable Connection Equipment No.

1


Suitable Mounting Technology No.

300



1 = Switching Status Indicator  
All dimensions in mm (1 mm = 0.03937 Inch)

1021



| Legend    |                                            |                                        |                                |
|-----------|--------------------------------------------|----------------------------------------|--------------------------------|
| +         | Supply Voltage +                           | nc                                     | Not connected                  |
| -         | Supply Voltage 0 V                         | U                                      | Test Input                     |
| ~         | Supply Voltage (AC Voltage)                | Ů                                      | Test Input inverted            |
| A         | Switching Output (NO)                      | W                                      | Trigger Input                  |
| Ā         | Switching Output (NC)                      | W-                                     | Ground for the Trigger Input   |
| V         | Contamination/Error Output (NO)            | O                                      | Analog Output                  |
| Ȳ         | Contamination/Error Output (NC)            | O-                                     | Ground for the Analog Output   |
| E         | Input (analog or digital)                  | BZ                                     | Block Discharge                |
| T         | Teach Input                                | Amv                                    | Valve Output                   |
| Z         | Time Delay (activation)                    | a                                      | Valve Control Output +         |
| S         | Shielding                                  | b                                      | Valve Control Output 0 V       |
| RxD       | Interface Receive Path                     | SY                                     | Synchronization                |
| TxD       | Interface Send Path                        | SY-                                    | Ground for the Synchronization |
| RDY       | Ready                                      | E+                                     | Receiver-Line                  |
| GND       | Ground                                     | S+                                     | Emitter-Line                   |
| CL        | Clock                                      | ⊕                                      | Grounding                      |
| E/A       | Output/Input programmable                  | SnR                                    | Switching Distance Reduction   |
| IO-Link   | IO-Link                                    | Rx+/-                                  | Ethernet Receive Path          |
| PoE       | Power over Ethernet                        | Tx+/-                                  | Ethernet Send Path             |
| IN        | Safety Input                               | Bus                                    | Interfaces-Bus A(+)/B(-)       |
| OSSD      | Safety Output                              | La                                     | Emitted Light disengageable    |
| Signal    | Signal Output                              | Mag                                    | Magnet activation              |
| BL_D+/-   | Ethernet Gigabit bidirect. data line (A-D) | RES                                    | Input confirmation             |
| ENo RS422 | Encoder 0-pulse 0/0 (TTL)                  | EDM                                    | Contact Monitoring             |
| PT        | Platinum measuring resistor                | ENARs422                               | Encoder A/Ā (TTL)              |
|           |                                            | ENBRs422                               | Encoder B/B̄ (TTL)             |
|           |                                            | ENA                                    | Encoder A                      |
|           |                                            | ENB                                    | Encoder B                      |
|           |                                            | AMIN                                   | Digital output MIN             |
|           |                                            | AMAX                                   | Digital output MAX             |
|           |                                            | AOK                                    | Digital output OK              |
|           |                                            | SY In                                  | Synchronization In             |
|           |                                            | SY OUT                                 | Synchronization OUT            |
|           |                                            | OLt                                    | Brightness output              |
|           |                                            | M                                      | Maintenance                    |
|           |                                            | rsv                                    | Reserved                       |
|           |                                            | Wire Colors according to DIN IEC 60757 |                                |
|           |                                            | BK                                     | Black                          |
|           |                                            | BN                                     | Brown                          |
|           |                                            | RD                                     | Red                            |
|           |                                            | OG                                     | Orange                         |
|           |                                            | YE                                     | Yellow                         |
|           |                                            | GN                                     | Green                          |
|           |                                            | BU                                     | Blue                           |
|           |                                            | VT                                     | Violet                         |
|           |                                            | GY                                     | Grey                           |
|           |                                            | WH                                     | White                          |
|           |                                            | PK                                     | Pink                           |
|           |                                            | GNYE                                   | Green/Yellow                   |

## Mounting

