Karşılıklı Sensör
Alıcı

P12E002

Sipariş numarası



- **Aşırı kirlenmede sorunsuz çalışma**
- **Karşılıklı bir etkileşim söz konusu değildir**
- **LV250 tipi kontrol cihazına bağlantı için**


Teknik Veriler

Optik veriler	
Işık türü	Kızılötesi
Kullanım ömrü (Tu = +25 °C)	100000 h
Müsaade edilen maks. harici ışık	10000 Lux
Açılma açısı	8 °
Elektriksel veriler	
Sensör tipi	Alıcı
Sıcaklık kayması	< 10 %
Sıcaklık aralığı	-25...60 °C
Kısa devre ve aşırı yük korumalı	Evet
Ters kutup korumalı	Evet
Koruma sınıfı	III
Mekanik veriler	
Gövde malzemesi	Pirinç, nikel kaplı
Tam korumalı gövde	Evet
Koruma sınıfı	IP67
Bağlantı türü	M8 × 1
Kablo uzunluğu	20 cm
LV250 tipi kontrol cihazına bağlantı için	●
Bağlantı şeması no.	118
Uygun sabitleme tekniği no.	170

Uygun vericiler

P12E001


Bu tek yollu ışık sensörleri LV250 tipi kontrol ünitesi ile birlikte çalışmaktadır. Tek yollu ışık sensörlerinin nereye yerleştirileceği serbestçe seçilebilmektedir. Bu cihazlar, geniş algılama mesafeleri nedeniyle aşırı kirli ortamlarda yüksek bir çalışma emniyeti ile çalışmaktadır.




Tamamlayıcı ürünler

Bağlantı kablosu ZCGL001

Control cihazı LV250



Ölçüler mm olarak verilmiştir (1 mm = 0.03937 inç)



Legend					
+	Supply Voltage +	nc	Not connected	ENBRS422	Encoder B/B̄ (TTL)
–	Supply Voltage 0 V	U	Test Input	ENA	Encoder A
~	Supply Voltage (AC Voltage)	Ū	Test Input inverted	ENB	Encoder B
A	Switching Output (NO)	W	Trigger Input	AMIN	Digital output MIN
Ā	Switching Output (NC)	W–	Ground for the Trigger Input	AMAX	Digital output MAX
V	Contamination/Error Output (NO)	O	Analog Output	AOK	Digital output OK
V̄	Contamination/Error Output (NC)	O–	Ground for the Analog Output	SY In	Synchronization In
E	Input (analog or digital)	BZ	Block Discharge	SY OUT	Synchronization OUT
T	Teach Input	AMV	Valve Output	OLT	Brightness output
Z	Time Delay (activation)	a	Valve Control Output +	M	Maintenance
S	Shielding	b	Valve Control Output 0 V	rsv	Reserved
RxD	Interface Receive Path	SY	Synchronization	Wire Colors according to DIN IEC 60757	
TxD	Interface Send Path	SY–	Ground for the Synchronization	BK	Black
RDY	Ready	E+	Receiver-Line	BN	Brown
GND	Ground	S+	Emitter-Line	RD	Red
CL	Clock	⏚	Grounding	OG	Orange
E/A	Output/Input programmable	SnR	Switching Distance Reduction	YE	Yellow
	IO-Link	Rx+/–	Ethernet Receive Path	GN	Green
PoE	ower over Ethernet	Tx+/–	Ethernet Send Path	BU	Blue
IN	Safety Input	Bus	Interfaces-Bus A(+)/B(–)	VT	Violet
OSSD	Safety Output	La	Emitted Light disengageable	GY	Grey
Signal	Signal Output	Mag	Magnet activation	WH	White
BI_D+/–	Ethernet Gigabit bidirect. data line (A-D)	RES	Input confirmation	PK	Pink
EN0 RS422	Encoder 0-pulse 0/0̄ (TTL)	EDM	Contactor Monitoring	GNYE	Green/Yellow
PT	Platinum measuring resistor	ENARS422	Encoder A/Ā (TTL)		

Teknik değişiklik yapma hakkı saklıdır