


Connection Cable

M12 × 1; Y-Distributor

ZDCG001

Part Number




All dimensions in mm (1 mm = 0.03937 Inch)

Technical Data

Mechanical Data

Connection 1	Socket, straight
Connection mode 1	M12 × 1, 12-pin
Connection 2	Plug, straight
Connection 2	Socket, straight
Connection mode 2	M12 × 1, 12-pin
Connection mode 2	M12 × 1, 4-pin
Cable Length	0,15 m
Outer diameter (d)	6,6 mm
Wire cross-section	0,14 mm ²
Degree of Protection	IP67
Temperature Range	-25...85 °C
Cable Jacket Material	PUR
Material Sleeve Nut	Zinc diecasting, nickel-plated
Screened	yes
Halogen-free	yes
Full Encapsulation	yes
Packaging unit	1 Piece
Connection Diagram No.	P10
Connection Equipment No.	87 02

- Plug M12 × 1, straight
- Screened
- Socket M12 × 1, straight



Legend					
+	Supply Voltage +	nc	Not connected	ENBRS422	Encoder B/B (TTL)
-	Supply Voltage 0 V	U	Test Input	ENA	Encoder A
~	Supply Voltage (AC Voltage)	Ü	Test Input inverted	ENB	Encoder B
A	Switching Output (NO)	W	Trigger Input	AMIN	Digital output MIN
Ä	Switching Output (NC)	W-	Ground for the Trigger Input	AMAX	Digital output MAX
V	Contamination/Error Output (NO)	O	Analog Output	AOK	Digital output OK
Ÿ	Contamination/Error Output (NC)	O-	Ground for the Analog Output	SY In	Synchronization In
E	Input (analog or digital)	BZ	Block Discharge	SY OUT	Synchronization OUT
T	Teach Input	AMV	Valve Output	QLT	Brightness output
Z	Time Delay (activation)	a	Valve Control Output +	M	Maintenance
S	Shielding	b	Valve Control Output 0 V	RSV	Reserved
RxD	Interface Receive Path	SY	Synchronization	Wire Colors according to DIN IEC 60757	
TxD	Interface Send Path	SY-	Ground for the Synchronization	BK	Black
RDY	Ready	E+	Receiver-Line	BN	Brown
GND	Ground	S+	Emitter-Line	RD	Red
CL	Clock	±	Grounding	OG	Orange
E/A	Output/Input programmable	SnR	Switching Distance Reduction	YE	Yellow
IO-Link	IO-Link	Rx+/-	Ethernet Receive Path	GN	Green
PoE	Power over Ethernet	Tx+/-	Ethernet Send Path	BU	Blue
IN	Safety Input	Bus	Interfaces-Bus A(+)/B(-)	VT	Violet
OSSD	Safety Output	La	Emitted Light disengageable	GY	Grey
Signal	Signal Output	Mag	Magnet activation	WH	White
BI_D+/-	Ethernet Gigabit bidirect. data line (A-D)	RES	Input confirmation	PK	Pink
ENo RS422	Encoder 0-pulse 0/0 (TTL)	EDM	Contact monitoring	GNYE	Green/Yellow
PT	Platinum measuring resistor	ENARIS422	Encoder A/A (TTL)		